

INV-L-125C

STAND ALONE INVERTER (CASSETTE)



POSITIVE PROBLEM SOLVING **+ =**

The INV-L-125C inverter can be specified to operate from a wide variety of DC Inputs.

These compact units utilise the same technology as their larger counterparts even though the output power is relatively low at 125VA. This range features a true sinewave output which is generated by a dedicated microprocessor. Overload and short circuit protection are built in as standard. LEDs are provided to show the operating status of the inverter. An alarm output signal is available in the form of voltage free contacts.

- + Provided as Pluggable 3U Rack Mount Cassette
- + Also Available in Bench & Wall Mount Cases
- + Short Circuit & Overload Protected
- + With 50Hz Output Transformer
- + Sinewave Output
- + Potential Free

INV-L-125C

STAND ALONE INVERTER (TABLETOP CASING)

FURTHER DETAILS

The INV-L-125C is housed in a 3U cassette, designed to be plugged into a 19" rack via a 15-pin connector. In all case formats these robust inverters carry a twenty-four month guarantee. The wide operating temperature range helps to ensure that the INV-L series is suitable for an extensive number of professional applications.

SELECTION TABLE

Part Number	Maximum Power ¹	Input Voltage	Output Voltage ²	Output Frequency ²
INV-L-125C 24	125VA	24VDC	230VAC	50Hz
INV-L-125C 24-1	125VA	24VDC	115VAC	60Hz
INV-L-125C 48-60	125VA	48/60VDC	230VAC	50Hz
INV-L-125C 48-60-1	125VA	48/60VDC	115VAC	60Hz

¹This is the maximum continuous apparent power at max PF. ²Different output voltage and frequencies are possible. Please contact ETPS to discuss your requirements.

TECHNICAL DATA

GENERAL

Electrical Safety	EN 60950, VDE 0805 (overload & short-circuit protected)
Efficiency	Approx. 85% by nominal load
Galvanic Isolation	3.75 kVDC
EMC (Emission)	EN 50081-1, Curve EN 55022B
EMC (Immunity)	EN 50082-2
Operating Temperature	-5 to +40°C (non-condensing)

INPUT DC

INV-L-125C 24	24 [19 - 31]VDC
INV-L-125C 48-60	48/60 [38 - 72]VDC

OUTPUT AC


Voltage	230VAC (optionally 115VAC)
Frequency	50Hz (optionally 60Hz)
Maximum Continuous True Power	100W
Permissible Power Factor	-0.8 to +0.8
Maximum Continuous Apparent Power	125VA
Load Range	0 - 100%
Crest Factor	>2.0
Harmonic Distortion	<5%

HOUSING

Casing	19" x 3U pluggable sub unit
Size	107 x 170 x 129mm (W x H x D)
Weight	Approx. 2.5kg
Classification	IP 20
Ventilation	Convection

ELECTRICAL CONNECTIONS

Rear Connectors	Appliance outlet EN 60320
-----------------	---------------------------



OTHER

Optical Signals	Power on/PG, Overload/OVL
Signal Output	Voltage free alarm contact for loss of output
Warranty	2 Years

Every effort is made to ensure that the information provided within this technical summary is accurate. However, ETPS Ltd must reserve the right to make changes to the published specifications without prior notice. Where certain operating parameters are critical for your application we advise that they be confirmed at the time of order. ETPS Ltd specialises in modifying its proven platforms to suit your needs. Please contact our office if your requirement is non-standard. Please note that your actual unit may differ from those shown.



“
**WE ARE
POSITIVE
PEOPLE**
”

ETPS engineer electronic power supply and testing systems. Our problem solving skills provide the spark of innovation to some of the world's leading technology brands.



Tel: +44 (0) 1246 452909
Sales: 0800 612 95 75
sales@etps.co.uk
www.etps.co.uk

ETPS Ltd
Unit 14, The Bridge
Beresford Way, Chesterfield
S41 9FG



POSITIVE PROBLEM SOLVING